

SolSwitch™-2000

For Single or Multi-site Corporations



- Up to 1,000 devices/users
- Intel Xeon
- Hot-swap HDD
- Multi-site Ready

Overview

The SolSwitch-2000 is capable of supporting large multi-site operations. Our SS2000 model provides for added reliability with dual power supplies and hot-swappable hard drives.

An IP-based phone system, all SolSwitch models come with a set of standard phone system features with the option of upgrading to the Advanced Features.

This 1U rackmount device supports up to 1,000 users, has no extension or voicemail limit and is compatible with a wide-range of devices and services – giving you total control over the functionality of your telephone system.

SIP-ready and fully compliant to the SIP standard, the SolSwitch has the ability to integrate with analog lines and/or devices.

All SolSwitch models come with a 2-year warranty with the option to purchase a 5-year extended warranty.

In the Box

- SolSwitch-2000
- 2 x Power Cables
- 2 x 6' Cat5e Patch Cables

SIP Compatibility

- Adtran Total Access Series, Total Access E Series, Net Vanta Series
- AudioCodes Mediant Series SBCs and Gateways
- Algo 8180
- Cisco SPA-122, SPA-122, SPA2102, SPA-504G, SPA-509G, SPA-514G, SPA-525G, SPA-922, SPA-942
- Grandstream HT701, HT702, HT704, HT802, DP715
- Mitel 6755i, 6757i, 6863i, 6865i, 6867i, 6869i, 9143i
- Panasonic UT123, UT133, UT136, TGP600 (cordless)
- Polycom SoundPoint IP-335, IP-450, IP-550, IP-560, IP-650, IP-670, VVX-300, VVX-310, VVX-400, VVX-410, VVX-500, VVX-1500, SoundStation 5000, SoundStation 6000, SoundStation 7000

Hardware Specifications

- CPU: 1 x Intel Xeon 2.4Ghz
- Cores/CPU : 10 Cores
- HDD: 2 x 4TB (RAID 1)
- Storage: 4TB
- Memory: 32GB
- Ethernet: 4 x Gigabit Ethernet
- Form Factor: 1U Rackmount
- Dimensions: 437mm x 754mm x 43mm (W x D x H)
- Power Supply: Dual 750W Redundant Supplies